TX-NR6100 7.2-Channel THX Certified Network A/V Receiver



Massive THX[®] sound and filmlike 8K resolution

Building key noise-reduction refinements into THX[®] Certified Select high-current amplification, the TX-NR6100 sets the bar for reference sound while bringing 8K/60p and HDR10+ video to your compatible display over HDMI®. Enjoy Dolby Atmos® and DTS:X® soundtracks through your height-enabled surround system or use upmixing and virtualization solutions from DTS® and Dolby® to create a 3D sound-field from any layout. Cue and control music around your home with voice assistants Ok Google or Alexa, and connect a second display via HDMI Sub/Zone 2 output. Chromecast built-in™, AirPlay 2, DTS Play-Fi®, and Works with Sonos cover every multi-room situation, and if you connect passive loudspeakers, you can switch between a 7.2/5.2.2-ch and 5.2-ch + Zone 2 layout at the touch of a button via Zone 2 speaker terminals. Features such as a quality MM phono equalizer and bi-directional Bluetooth® wireless technology make this value proposition even more persuasive.

PRODUCT HIGHLIGHTS

- 175 W/Ch THX® Certified Select DAA system

- S.2.2-ch Dolby Atmos[®] and DTS:X[®] playback
 SMART AV Receiver[™] Works with Sonos^{*1}, Chromecast built-in[™], AirPlay 2, and DTS Play-Fi[®]; includes Spotif[®], Amazon Music HD^{*2}, TIDAL, Deezer, and Tuneln streaming services^{*3}
- Works with Ok Google or Alexa*4
- Stream over 5 GHz/2.4 GHz dual-band Wi-Fi® supporting the 802.11ac standard¹⁵
- HDMI® inputs 1-3 and Main/Sub outpus support 8K/60p(4:2:0/10-bit), 8K/30p(4:4:4/10-bit), 4K/120p(4:4:4/10-bit) video pass through
- HDMI terminals⁷⁷ support HDR10+, Dolby Vision and BT.2020 color; VRR (Variable Refresh Rate), ALLM (Auto Low Latency Mode), and QFT (Quick Frame Transport) passthrough; eARC (Main Out), and HDCP 2.3
- HDMI Sub/Zone 2 Out for media transmission to a projector, gaming monitor, or TV
- Send or receive audio via *Bluetooth®* wireless technology (RX mode: SBC/AAC, TX mode: SBC/Qualcomm® aptX[™]/ aptX HD)
- Refined chassis, HDMI board, DAC, Digital/Analog inputs, power-amp grounds and power lines
- Zone 2 speaker posts for powered D/A audio distribution (including HDMI/SPDIF/NET*6) to passive speakers
- Zone 2/Zone B line-out (analog RCA) with Zone 2 DAC supports independent or synced D/A playback (including HDMI/SPDIF/NET^{*6}) on compatible audio systems • AccuEQ with AccuReflex[™] and subwoofer EQ

AMPLIFIER FEATURES

- 175 W/Ch (6 Ω, 1 kHz, 10% THD, 1 channel driven), 165 W/Ch (6 Ω, 1 kHz, 1% THD, 1 channel driven, IEC)
- THX Certified Select
- Onkyo Dynamic Audio Amplification (DAA)
- Discrete 2-stage non-phase-shift amplifier circuitry
- Custom High-Current Low-Noise Power Transformer
- Large custom-made audio-grade power capacitors
- · Strengthened power supply line supports high-current dynamics Refined chassis, HDMI board, DAC, Digital/Analog inputs, power-amp
- grounds and power lines
- · Isolated network module reduces high-frequency signal interference on audio circuitry High current capability drives 4-ohm loads through 7 channels
- Precision 192 kHz/24-bit D/A conversion for Hi-Res Audio VLSC[™] (Vector Linear Shaping Circuitry) filtering (Front L/R)
- PLL (Phase Locked Loop) anti-jitter technology for SPDIF audio
- · Tone controls (bass/treble) for front L/R channels

VIDEO & AUDIO SUPPORT

- Supports features defined in HDMI 2.1⁻⁷ specification including 8K/60p(4:4:4/12-bit⁻⁹, 4:22/12-bit⁻⁹, 4:20/10-bit), 8K/30p(4:4:4/12-bit⁻⁹, 4:4:4/10-bit, 4:22/12-bit), 4K/120p(4:4:4/12-bit⁻⁹, 4:4:4/10-bit, 4:22/12-bit) video passthrough, VRR, ALLM, QFT (Quick Frame Transport), DSC (Display Stream Compression), QMS (Quick Media Switching) and eARC (Main Out); supports HDR10+, Dolby Vision[™], HDR10, and HLC, and BT.2020 color; DeepColor[™], xx.Color[™], LipSync, and HDCP 2.3
- Dolby Atmos, DTS:X, Dolby[®] TrueHD, and DTS-HD
- Master Audio® decoding Dolby Atmos Height Virtualizer and DTS Virtual:X 3D processing

- Dolby Surround® and DTS® Neural:X 3D upmixing technologies
 Hi-Res Audio playback via network and USB including DSD256, DSD128, DSD64 (DSDIFF/DSF) and 192 kHz/24-bit FLAC, ALAC, WAV (RIFF), and AIFF*9
- SACD (Super Audio CD) playback via HDMI (2.8 MHz 2-ch/multichannel)
- Theater-Dimensional virtual surround-sound function
- Sound optimization for games (Rock, Sports, Action, and RPG)
- NETWORK FEATURES
- SMART AV Receiver platform with integrated streaming services, voice assistant support, and control via remote apps
- Fast quad-core SoC supports 802.1 lac (2x2 MIMO) Wi-Fi Works with Sonos for the Sonos Home Sound System with Sonos
- app*
- Works with Alexa supporting multi-room music*11
 Works with Ok Google and Chromecast built-in
- Supports Apple AirPlay 2 enabling Siri voice control
- DTS Play-Fi multi-room audio via Onkyo Music Control App*10
- Control and manage multiroom playback with Onkyo Controller app^{*10}
- · Roon Tested certification for the Roon Core
- IP Control for setup via PC and integration into a hom
- tion system

CONNECTION FEATURES

- 6 HDMI inputs and 2 outputs (Main Out [eARC], Sub/Zone 2 Out)
- 2 digital audio inputs (optical and coaxial, assignable)
 4 analog RCA audio inputs (assignable)
- I phono input with built-in MM phono equalizer 3.5 mm mic input for AccuEQ setup
- 6.35 mm headphone jack
- 2 subwoofer pre-outs
- Zone 2/Zone B analog RCA line-level out/Front L/R pre-out
- 7 speaker binding posts
- I0BASE-T/I00BASE-TX Ethernet terminal for network connection USB inputs (front:DC 5V/500 mA, rear:DC 5 V/1 A) for audio playback
- · AC inlet for detachable IEC power cord

ADVANCED FEATURES

AccuEQ Room Acoustic Calibration with AccuReflex and subwoofer EQ Bluetoot wireless technology supports audio reception from mobile devices and PC, audio transmission to supported headphones (RX mode: SBC/AAC, TX mode: SBC/aptX/aptX HD)
 Advanced Music Optimizer[™] improves compressed audio

ONKYO

- playback quality
- Wake on Play standby for Bluetooth and Network with auto input-switching
- Vocal Enhancer boosts vocals/dialog audibility via remote control or FM and DAB/AM tuner with 40 random station memory presets
- Zone 2 DAC for independent D/A audio distribution (HDMI/SPDIF/NET)
- Zone 2 speaker outputs (shared with Height/Surround Back/Bi-amp) distribute powered D/A audio (including HDMI/SPDIF/NET*) to passive speakers
- Zone 2 line-out^{e12} connects compatible components for independent or synced D/A playback (including HDMI/SPDIF/NET⁶)
- Zone B line-out^{*12} connects compatible wireless headphone docks for synced playback with MAIN Zone^{*6}
- Front L/R pre-outs*12 support external power amp connection
- Switch from Front L/R speakers to Height/Surround/Surround Back speakers using Stereo Assign Mode*13 for BGM listening
- My Input Volume one-touch startup volume assignment to individual inputs
- High-definition GUI with overlaid OSD over HDMI
- 4K to 8K, 1080p to 8K/4K video upscaling via HDMI
- · OSD function shows source data and playback settings
- Crossover adjustment for each channel (40/50/60/70/80/90/100/120/150/180/200 Hz)
- A/V Sync Control (up to 500 ms in 5 ms steps at 48 kHz*14) Various standby modes and HDMI pass-through
- 3-Mode display dimmer (Normal/Dim/Dimmer)

*1 Requires a Sonos Connect or Port (sold separately). Connection of 1–2 Sonos devices is supported with volume control enabled via the Sonos app for IOS and Andraid" devices. *2 Amazan Music HD is supported via DTS Play-Fit +3 Streaming service availability may vary by region. An account and subscription may be required for some streaming services. *4 Vaice control requires on Alexa built-in or Goagle Assistant enabled device, such as a samt stpeaker or smartphone. Interoperability with streaming services depends on the respective technology and the country or region. *5 Some countries or regions have regulations that affect wireless signal-strength and use [Vi-Ri channels. *6 When set to Zone 2 mode. HDMI audo is available on inputs 1–3. SPDF and HDMI support 2-di PCM signals only, and simultaneous playback of playback for all inputs is enabled in MAIN and Zone B mode, enaded and PCM audo playback for all inputs 1–3. Man Out, and subJCane 2 Out in sub Mode output- #8 DSC (Display Stream Campression) signals only, "Bupported are supported on HDMI inputs 1–3. HAM. "L. *10 Available free for inhome and iPad the App Store. Available free for Andraid devices and Singular output and the App Store. Available free for inhome. 111 Multi-room music may require differe standards." In Man Dut, Rie mout, and SubJCane 2 Dut in sub, requering the store is maximum 96 KHz. *110 Available free for inhome update. *12 Cane 2 line-out, Zane B line-out, and Front UR pre-out are exclusive modes shared on the same analog RCA output. *13 Specification of provide and Front UR pre-out are exclusive modes shared on the same analog RCA output. *14 Max. 400 ms (5 ms steps) at 96 kHz, and max. 200 ms (5 ms steps) at 12 kHz.

THX® Certified Select cinema-reference sound

THX Certified Select guarantees the same reference volume and sound quality of a commercial cinema in rooms where the screen-to-seat distance is about 3.5 m. THX® certified receivers must pass 2,000 bench-tests in 75 categories



Welcome to the 8K Ultra HD experience

Features defined in HDMI® 2.1 specification enable 8K/60p video passthrough to your compatible display. As well as HDR10 and HLG, HDR10+ and Dolby Vision™ formats optimize brightness, contrast, and color scene-by-scene or frame-by-frame. All HDMI terminals support HDCP 2.3, while eARC on Main Out passes encoded multichannel audio (including Dolby Atmos® or DTS:X®) from your compatible TV's tuner, video streaming apps, or connected media players to the AVR for amplification. QMS (Quick Media Switching) for movies and video eliminates the delay that can result in a blank screen before content is displayed.

Note: 8K video passthrough is not supported on HDMI inputs 4–6 and Sub/Zone 2 Out.

New enhancements for gamers

Transform your playtime with 3D surround-sound and gain the winning edge with new gamer-friendly features defined in HDMI 2.1. VRR (Variable Refresh Rate) eliminates lag, stutter, and frame-tearing for fluid gameplay. ALLM (Auto Low Latency Mode) optimizes latency from source to screen while QFT (Quick Frame Transport) limits lag for a smoother experience

SMART AV Receiver[™] multi-room audio streaming

SMAR

AV RECEIVER

SMART AV Receiver shares audio around your home. It includes Amazon Music HD*, Spotify[®], TIDAL, Deezer, and Tuneln, and works with Ok Google or Alexa. Share entertainment via Works with Sonos, AirPlay

2, DTS Play-Fi®, and Chromecast built-in. * Amazon Music HD is supported via DTS Play-Fi.

Works with Sonos

Expand your Sonos Home Sound System by pairing this AVR to a Sonos Connect or Port". The receiver ties into the Sonos ecosystem, waking, changing inputs, and playing at the desired volume on command from the Sonos app*.

* Sonos Connect and Port sold separately. Sonos app available free for iPhone and iPad from the App Store, and for Android[™] devices on Google Play.

Chromecast built-in[™] works with Ok Google

Stream music from your smartphone, laptop, or PC to the receiver via Chromecast built-in and control playback from Chromecast-enabled apps from iPhone, iPad, Android[™] phone or tablet, Mac or Windows® PC, or Chromebook™. Cue, play, and control audio just by using your voice.

Works with Alexa

Alexa lets you use your voice to control the A/V receiver by speaking commands through an Alexa built-in device. Whether you want to listen to music, radio stations, or podcasts, all you have to do is ask. It also supports multi-room music* played on multiple devices.

* Multi-room music may require a firmware update

Dolby Atmos and DTS:X celebrate a new world of sound

Dolby Atmos and DTS:X translate 3D soundtracks from the studio mixing desk to your living room. Sounds are no longer tied to specific channels, and are free to move around and above your audience, placing them at the heart of the action.

Enjoy legacy formats with 3D sound

Dolby Atmos Height Virtualizer and DTS Virtual:X[™] deliver 3D sound through any listener-level speaker layout. The

technologies can work independently or with Dolby Surround® or DTS® Neural:X upmixers to create a 3D sound-field with any audio signal (excluding Dolby Atmos, DTS:X, and



5 GHz/2.4 GHz dual-band Wi-Fi® supports the 802.1 lac standard

A powerful quad-core SoC (System on a

Chip) performs multiple processing tasks

at once. It evolves network functions and supports the 802.1 Lac (2x2 MIMO) standard for stable multi-room audio streaming.

 \ast Note: some countries or regions have regulations that affect wireless signal strength and the use of Wi-Fi channels.

Clearer dialog at the touch of a button

Vocal Enhancer solves the problem of inaudible dialog in movies and TV programs by using DSP algorithms to elevate vocal frequencies in the soundtrack. The effect level can be raised or lowered using keys on the remote control.

AccuEQ room acoustic calibration

Detects speaker size, crossover frequency, and distance from the listening position and sets appropriate sound-pressure levels. Sets crossover and EQs all speakers including the subwoofers. AccuReflex™ optimizes 3D sound through Dolby Atmos-enabled speakers by correcting phase differences in directional and non-directional sound-paths. The result is a clear and cohesive sound-field.

Bi-directional Bluetooth® wireless technology

This AVR can send and receive audio via Bluetooth wireless technology. Stream from your device to the receiver using SBC or AAC codecs, or transmit audio playing through the AVR to compatible wireless headphones using SBC, aptX[™], or aptX HD codecs including 24-bit audio over aptX HD. Note: supports MAIN Zone source transmission (excludes Chromecast built-in and Works with Alexa). Lossless 24-bit audio requires headphones supporting aptX HD.

Zone 2 outputs for powered multi-room audio

Height/Surround Back/Bi-amp speaker posts can be configured for Powered Zone 2 audio distribution in addition to a 5.2-ch layout. Sync one source or play two sources (including analog, HDMI, SPDIF, and NET) in both rooms simultaneously. Note: HDMI and SPDIF supports 2-ch PCM only. HDMI available on inputs 1-3Output from Zone 2 line-out is enabled.


Multi-function Zone 2 or Zone B line-out

Analog RCA line-out terminal is served by a Zone 2 D/A converter and supports two Zone audio modes: Zone 2 supports active speaker or hi-fi system connection. Sync a source in MAIN and Zone 2, or play two unique sources simultaneously. Zone B suits wireless headphone docks. Enjoy MAIN Zone audio source through your wireless headphones. This terminal also supports Front L/R pre-out to an external hi-fi power amplifier.

Note: in Zone 2 mode, HDMI audio is a support 2-ch PCM signals only. In Zone I inputs) is enabled in MAIN and Zone B. ode, HDMI audio is available on inputs 1–3 and SPDIF and HDMI signals only. In Zone B mode, encoded and 2-ch PCM audio (all

Relax with Stereo Assign Mode

Stereo Assign Mode switches playback from Front to Height, Surround, or Surround Back speakers depending on your layout. Ideal for ambient background listening.



SI



SPECIFICATION	13
Amplifier Section	
Power output (All channe	els)
	175 W/Ch
	(6 Ω, 1 kHz, 10% THD, 1-ch driven)
	165 W/Ch
	(6 Ω, 1 kHz, 1% THD, 1-ch driven, IEC)
Dynamic power	240 W (3 Ω, Front)
Dynamic power	210 W (4 Ω, Front)
	120 W (8 Ω, Front)
THD+N (Total Harmonic	
	0.08% (20 Hz–20 kHz, half power)
Input sensitivity and impe	dance
	200 mV rms/47 kΩ (Line)
	3.5 mV rms/47 kΩ (Phono MM)
Rated RCA output level a	
raced ries i output lever a	I V rms/470 Ω (Subwoofer pre-out)
	200 mV rms/2.2 k Ω (Zone 2/Zone B line-out)
Frequency response	10 Hz–100 kHz/+1 dB, -3 dB (Direct Mode)
Tone control	±10 dB, 20 Hz (Bass)
	±10 dB, 20 kHz (Treble)
Signal-to-noise ratio	106 dB (Line, IHF-A)
	80 dB (Phono, IHF-A)
C	4–16 Ω
Speaker impedance	*=10 12
Tuner Section	
Tuning frequency range	
DAB (Europe)	174,928 MHz-239,2 MHz
FM	87.5 MHz-108 MHz
AM (Asia & Oceania)	
, and , old of Occaria)	530 kHz–1,710 kHz
DAD/DM/AM	
DAB/FM/AM preset mem	
	40 stations
General	
Power supply	AC 220-240 V~, 50/60 Hz
Power consumption (ope	
Power consumption (ope	
	570 W
Power consumption (idle) 65 W
Power consumption (stan	idby)
	0.15 W
Dimensions (W x H x D)	435 v 173 5 v 379 5 mm
Weight	9.8 kg
CARTON	
Dimensions (W x H x D)	534 x 265 x 468 mm
	12.5 kg
Weight	IZ.J Kg

Supplied Accessories

 Power cord • Indoor DAB/FM antenna • AM loop antenna
 Speaker setup microphone • Quick Start Guide • Remote controller AAA (R03) batteries x 2



Text on receiver may vary with regio

Due to a policy of continuous product improvement, Onkyo reserves the right to change specifications and appearance without notice. THX and the THX Logo are the property of THX Ltd, registered in the U.S. and other countries. Dolby Atmos, Dolby Surround, Dolby Vision, and the double-D symbol are trademarks of Dolby Laboratories. For DTS patents, see http://patents.dts.com. Manufactured under license from DTS Licensing Limited. DTS, the Symbol, DTS and the Symbol together, DTSX and the DTS VirtualX and the DTS VirtualX togo, DTS NeuralX and the DTS NeuralX and the DTS Express and the DTS Express logo, and Pay-Fi and the Pay-Fi logo are registered trademarks of DOS is a trademark of SONOS, Inc. The Bluetooth® word mark and logos are owned by the Bluetooth SIG, Inc. Apple, AirPlay, Sin, Mac, iPad, and iPhone are trademarks of Apple Inc, registered in the U.S. and other countries. App Store is a service mark of Apple Inc. Google, Android, Google Play, Chromebook, and other related marks are trademarks of Dostify Logo are trademarks of Apple Inc, registered in the U.S. and other countries. Postfy Goog on trademarks of Apple Inc. Google, Android, Google Play, Chromebook, and other related marks are trademarks of Dostify Goog are trademarks of Apple Inc, registered in the U.S. and other countries. Postfy Goog on: a trademark of Robit Google, Play, Philaes Nation Boogle Dis used under license from Japa Audio Society. Amazon, Alexa and al related logos are trademarks of Amazon.com, Inc. or its affiliates, Qualcomm is a trademark of Qualcomm Incorporated, registered in the United States and other countries. Spotify Goog on: trademarks of Apple Inc. Google Inter Miland. Ltd., registered in the United States and other countries. Postfyr Googne trademarks of Apple Inc. Google Play, Chromebook, and other license from Japa Audio Society. The Hinters Audio logo is used under license from Japa Audio Society. The Hinters Audio Internative Audio Angle Society. The Hinters Audio Internative Audio Internative Audio Angle Society. T

