
I / O 6

6.5" 2-WAY OUTDOOR SPEAKER

Jamo[®]



SPECIFICATIONS

FREQUENCY RESPONSE	67Hz - 18kHz
POWER HANDLING	50W RMS / 100W Peak
NOMINAL IMPEDANCE	4 Ohm
SENSITIVITY	89dB
LOW FREQUENCY DRIVER	165mm (6.5") Aluminum HCC
HIGH FREQUENCY DRIVER	25mm (1") Aluminum Dome
ENCLOSURE MATERIAL	UV Resistant ABS
ENCLOSURE TYPE	Sealed Enclosure
INPUTS	Single Binding Posts
DIMENSIONS (MM / IN, HxWxD)	215 x 229 x 339 / 8-7/16" x 9" x 13-3/8"
WEIGHT (KG/LBS)	3.4 / 7.5
FINISHES	Satin Black, Satin White

DESIGN + PERFORMANCE

The smooth lines, satin painted finish, and compact design of the I/O 6 allows it to blend seamlessly into even the most luxurious of outdoor living space, while the 6.5" long-throw aluminum HCC woofer and 1" aluminum tweeter provide detailed, dynamic, balanced sound.

EASY, ROBUST INSTALLATION

The new Jamo I/O series features an ultra durable powder coated steel C-bracket for simple, easy, and reliable installation in any outdoor environment.

ALL WEATHER DURABILITY

A powder coated grille mated to a UV-resistant, ABS cabinet provides the utmost in all-weather capability. The new Jamo I/O series is designed and built to offer great outdoor audio year in and year out.