

# SKS-HT588 5.1.2-Channel Home Cinema Speaker System



BLACK

## Experience the Magic of Next-Gen Cinema Sound

This six-piece speaker package reproduces everything from multidimensional Dolby Atmos® soundtracks to MP3s streamed from your phone with utmost precision. Two-way front speakers feature large paper-cone woofers and balanced-dome tweeters to articulate wide-spectrum audio with timing, clarity, and scale. They include an upfiring driver housed in a compartment in the top of the cabinet which bounces “sound objects” contained in Dolby Atmos and DTS:X™ soundtracks off the ceiling and into the audience, convincingly replicating sounds that originate from overhead. Joining two compact, wall-mountable surround-sound speakers and the dual-drive 2-Way center speaker is a powerful 10-inch subwoofer delivering up to 80 W of wall-shaking bass. Finished in elegant black hairline, the SKS-HT588 package is the most convenient way to get immersed in next-generation cinema sound magic.

### SKF-2800 Dolby Atmos®-Enabled Integrated Front & Height Speakers

- 12 cm Cone Woofer
- 2.5 cm Balanced-Dome Tweeter
- 8 cm Cone (Separately Powered By Height Channel)
- Max. Input Power: 130 W
- Wall-Mounting Capability

### SKC-594 2-Way Bass Reflex Center Speaker

- 8 cm Cone Woofer x 2
- 2.5 cm Balanced-Dome Tweeter
- Max. Input Power: 130 W
- Wall-Mounting Capability

### SKR-594

#### Full-Range Acoustic-Suspension Surround Speakers

- 8 cm Cone
- Max. Input Power: 130 W
- Wall-Mounting Capability

### SKW-658 Bass Reflex Powered Subwoofer

- 20 cm Cone
- Rated Output Power: 80 W (Minimum Continuous Power, 4 Ω, 100 Hz, 1%, IEC)
- Energy-Saving High Power Amplifier
- Down-Firing Design

## SPECIFICATIONS

### SPEAKER SYSTEM

Speaker Type	
Front	2-Way, Bass Reflex
Height	Full-Range, Acoustic-Suspension
Center	2-Way, Bass Reflex
Surround	Full-Range, Acoustic-Suspension
Subwoofer	Bass Reflex, Powered
Drivers	
Front	12 cm Cone Woofer
Height	2.5 cm Balanced-Dome Tweeter
Center	8 cm Cone
Surround	8 cm Cone Woofer x 2
Subwoofer	2.5 cm Balanced-Dome Tweeter
Subwoofer	20 cm Cone
Frequency Response	
Front	55 Hz–50 kHz
Height	80 Hz–20 kHz
Center	65 Hz–50 kHz
Surround	80 Hz–20 kHz
Subwoofer	27 Hz–150 Hz
Output Sound Pressure Level	
Front	83 dB/W/m
Height	81 dB/W/m
Center	86 dB/W/m
Surround	81 dB/W/m
Max. Input Power	
Front/Height/Center/Surround	130 W

Rated Output Power	80 W (Minimum Continuous Power, 4 Ω, 100 Hz, 1%, IEC)
Subwoofer	
Nominal Impedance	Front/Height/Center/Surround 6 Ω
Input Sensitivity/Impedance	440 mV/20 kΩ
Subwoofer	
General	
Dimensions (W x H x D)	
Front/Height	155 x 467 x 183 mm
Center	409 x 115 x 121 mm
Surround	115 x 230 x 96 mm
Subwoofer	230 x 425 x 410 mm
Weight	
Front/Height	3.7 kg
Center	2.2 kg
Surround	1.0 kg
Subwoofer	7.7 kg
CARTON	
Dimensions (W x H x D)	772 x 584 x 514 mm
Weight	24.0 kg
Supplied Accessories	
• Color-coded speaker cables • Subwoofer cable	

Due to a policy of continuous product improvement, Onkyo reserves the right to change specifications and appearance without notice. Manufactured under license from Dolby Laboratories. Dolby Atmos and the double-D symbol are trademarks of Dolby Laboratories. Manufactured under license from DTS Licensing Limited. For DTS patents, see <http://patents.dts.com>. DTS, DTS-HD, the Symbol, & DTS and the Symbol together are registered trademarks, and DTS:X is a trademark of DTS, Inc. © DTS, Inc. All Rights Reserved. All other trademarks and registered trademarks are the property of their respective holders.